

di Ziliani Fabio e Cristina PRESSURE GAUGES Via Garibaldi n.119 – 46013 Canneto s/Oglio (MN) ITALY Tel. +39.0376.70125

Part. IVA n. 02059990206

## DESCRIPTION OF MATERIAL USED FOR DRY PRESSURE GAUGES

CASE: BLACK PLASTIC, BLACK VARNISHED STEEL, CROMED STEEL,

STAINLESS STEEL **THREAD:** BRASS

**SENSING ELEMENT:** BOURDON SYSTEM TUBULAR SPRING,

TOMBAC Cu/Zn15 MADE IN ITALY

**MOVEMENT:** CLOCKWORK BRASS MADE IN GERMANY

**SPRING - MOVEMENT CONNECTION: BRASS CONNECTING ROD** 

DIAL: WHITE VARNISHED ALUMINIUM WITH BLACK GRADUATIONS

**POINTER:** BLACK PLASTIC FOR DIAMETER 40/50/63,

BLACK ALUMINIUM FOR DIAMETER 80/100

TRASPARENT: PLEXIGLASS, NATURAL GLASS WITH CROMED BEZEL RING

WELDING: Sn97/Cu3 TEMPERATURE LIMIT -40+180°C

CALIBRATION: SINGLE, Kl. 1,6 FOR DIAMETER 50/63/80/100;

Kl. 2,5 FOR DIAMETER 40

**INSTRUMENTS USED FOR CALIBRATION: PRESSURE GAUGE** 

DN 160 Kl. 0.25 CALIBRATION EXECUTED EACH MONTH

ON HYDRAULIC DEADWEIGHT TESTERS MOD. LUCAS

PRESSUREMENTS M4000/1 N°7290-92

**ON REQUEST:** FOR TEMPERATURE TILL 200°C WE ASSEMBLE AN ALPACCA SPRING AND WELDING Sn95/Ag5

**BEST OPERATING PRESSURE:** 3/4 OF THE FULL SCALE FOR CONSTANT PRESSURES 2/3 OF THE FULL SCALE FOR CHANGEABLE PRESSURES

**OVER RANGE CAPACITY**: 25% FOR RANGE

## **CONFORMITY DECLARATION**

WE DECLARE THAT WE TEST AND CALIBRATE EACH LOT AT 100% WE DECLARE THAT OUR PRESSURE GAUGES ARE CONFERMED TO **NORM UNI EN 837-1** WITH THE APPLICATION OF DIRECTIVE 2014/68/UE (PED) THAT IMPOSE TO PRINT THE LOGO OF THE PRODUCER OR THE MANDATARY

## **DIRECTIVE RoHS 2011/65/EU (ed. Directive RoHS II)**:

WE DECLARE THAT OUR PRODUCTS DON'T CONTAIN MERCURY, CADMIUM, HEXAVALENT CHROMIUM AND THE 2 BROMINATED FLAME RETARDANT, PBB & PBDE.

THE CONTENT OF LEAD IN COPPER ALLOY COMPLIES WITH DIRECTIVE ROHS II.

THE PRODUCT IS ONLY MADE IN ITALY AND REALIZED WITH GERMAN, ITALIAN, SWISS ADVANCED MACHINARY